



# Non-Programmable Thermostat Selection Guide



Image	Model	Schedule Option	User Interface	Application				Power Method	Features and Functions						Display Information			Limited Warranty	Wiring Terminals	Replacements					
				Stages	Gas, Oil or Electric	Heat Pump	Millivolt		Linevolt	Permanent Memory Retention	Selectable Auto or Manual Chargeover	Advanced Dual Fuel Heat Pump operation	Comfort/Economy Mode	Temperature Setpoint Limits	Low Temperature Range	Remote Locator	Display Size (Viewable)			On-Demand Backlighting	Simultaneous Display of Room and Set Temperatures	Honeywell	White-Rodgers	Robenshaw®	Other
	YTH5320R1000	Non-Prog	Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•			Battery	•	•	•*	•	•		•	5.09 sq. in.	•	•	5 Year	C, R, Rc, Rh, W-0/B, W2-AUX/E, Y, Y2, G, L, RAS				
	TH5110D1006	Non-Prog	Soft Keys	1 Heat/1 Cool	•	•	•		Dual Powered (Battery and Hardwire)	•	•			•			1.95 sq. in.	•	•	5 Year	R, Rc, W-0/B, Y, G, C	T8501, T8400, T8401	1F86	8400, 8401, 9400, 9401, 9550	
	TH5110D1022	Non-Prog	Soft Keys	1 Heat/1 Cool	•	•	•		Dual Powered (Battery and Hardwire)	•	•			•			2.98 sq. in.	•	•	5 Year	R, Rc, W-0/B, Y, G, C	T8501, T8400, T8401	1F86	8400, 8401, 9400, 9401, 9550	
	TH5220D1003	Non-Prog	Soft Keys	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual Powered (Battery and Hardwire)	•	•	•	•				3.75 sq. in.	•	•	5 Year	R, Rc, W-0/B, AUX-W2, Y, Y2-E, L, G, C	T8501, T8511, T8524, T8400, T8401, T8411, T8424	1F73, 1F83, 1F86, 1F89	8400, 8401, 8425, 9400, 9401, 9415, 9420, 9550, 9555, 9560	
	TH5220D1029	Non-Prog	Soft Keys	Up to 2 Heat/1 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual Powered (Battery and Hardwire)	•	•	•	•				5.09 sq. in.	•	•	5 Year	R, Rc, W-0/B, AUX-W2, Y, Y2-E, L, G, C	T8501, T8511, T8524, T8400, T8401, T8411, T8424	1F73, 1F83, 1F86, 1F89	8400, 8401, 8425, 9400, 9401, 9415, 9420, 9550, 9555, 9560	
	TH5320U1001	Non-Prog	Soft Keys	Up to 3 Heat/2 Cool – Heat Pump Up to 2 Heat/2 Cool – Conventional	•	•	•		Dual Powered (Battery and Hardwire)	•	•	•	•				5.09 sq. in.	•	•	5 Year	R, Rc, W-0/B, W2-AUX/E, Y, Y2, G, L, C	T8501, T8511, T8524, T8400, T8401, T8411, T8424			
	TH3110D1008	Non-Prog	Slide Switches	1 Heat/1 Cool	•	•	•		Dual Powered (Battery and Hardwire)	•	Manual						1.32 sq. in.	•	•	5 Year	R, Rc, C, W, O, B, Y, G	T8400, T8401	1F78-144	8400, 9500	Breabum 3000; LUX PDS100, PDS111, PDS150
	TH3210D1004	Non-Prog	Slide Switches	2Heat/1 Cool Heat Pump		•			Dual Powered (Battery and Hardwire)	•	Manual						1.32 sq. in.	•	•	5 Year	R, C, Y, Aux, O, B, E, G, L	T8411R	1F79-111	8425, 9420	Breabum 3200; LUX PSDH105, PSDH121
	TH1110D1000	Non-Prog	Slide Switches	1 Heat/1 Cool	•	•	•		Dual Powered (Battery and Hardwire)	•	Manual						1.0 sq. in.	•	•	2 Year	R, C, W, O/B, Y, G	T8400, T8401	1F78-144	8400, 9500	Breabum 1000, 1005, 1010; LUX PDS100, PDS111, PSD150
	TH1100D1001	Non-Prog	Slide Switches	1 Heat	•	•			Dual Powered (Battery and Hardwire)	•	Manual		•	•			1.0 sq. in.	•	•	2 Year	R, C, W, O/B, Y, G	T8411R	1F79-111	8425, 9420	Breabum 1100, 1200; LUX PSDH105, PSDH121
	TH1210D1008	Non-Prog	Slide Switches	2Heat/1 Cool Heat Pump		•			Dual Powered (Battery and Hardwire)	•	Manual						1.0 sq. in.	•	•	2 Year	R, C, AUX/E, O/B, Y, G	T8411R	1F79-111	8425, 9420	Breabum 1100, 1200; LUX PSDH105, PSDH121
	T8775A1009	Non-Prog	Dial	1 Heat	•*				Power Stealing	•							.75 sq. in.	•		5 Year	R, W	T87F			
	T8775C1005	Non-Prog	Dial	1 Heat/1 Cool	•	•			Power Stealing	•	Manual						.75 sq. in.	•		5 Year	R, Rc, W, O, B, Y, G	T87F			
	T87K1007	Non-Prog	Dial	1 Heat	•*				Battery Assisted Power Stealing					50010944-001			N/A		•	5 Year	R, W	T87F			
	T87N1000	Non-Prog	Dial	1 Heat/1 Cool	•	•			Battery Assisted Power Stealing		Manual			50010944-001			N/A		•	5 Year	R, Rc, W, Y, G, O, B	T87F and Q539			
	T87N1026	Non-Prog	Easy-To-See™	1 Heat/1 Cool	•	•			Battery Assisted Power Stealing		Manual			50010944-001			N/A		•	5 Year	R, Rc, W, Y, G, O, B	T87F3467 and T87F5199			
	T834N1002	Non-Prog	Slide Switches and Lever	1 Heat/1 Cool	•	•			Mechanical		Manual			50019661-001			N/A			5 Year	R, Rc, W, Y, G, O, B	T834C	1E56, 1P56	9200, 400	
	T8034N1007	Non-Prog	Slide Switches and Lever	1 Heat/1 Cool	•	•			Mechanical		Manual			50019661-001			N/A			5 Year	R, Rc, W, Y, G, O, B	T8034C	1D56, 1F56	9200, 400	
	T822K1000	Non-Prog	Slide Switches and Lever	1 Heat	•*				Mechanical			Positive Off		50019661-001			N/A			5 Year	R, W	T822D	1E30	9204, 200	
	T822K1018	Non-Prog	Slide Switches and Lever	1 Heat	•*				Mechanical			•		50019661-001			N/A			5 Year	R, W	T822D	1E30	9204, 200	
	T822K1042	Non-Prog	Slide Switches and Lever	1 Heat	•*				Mechanical				•	50019661-001			N/A			5 Year	R, W	T822D	1E30	9204, 200	
	T827K1009	Non-Prog	Slide Switches and Lever	1 Heat			•*		Mechanical			Positive Off		50019661-001			N/A			5 Year	R, W	T827	1E30	9204, 400-404	
	TL7235A1003	Non-Prog	Horizontal Lays	1 Heat			•		208/240 V								2.67 sq. in.	•		5 Year	4 wire DPST				
	TL7230A1004	Non-Prog	Dial	1 Heat			•		208/240 V								N/A			5 Year	DPST				
	T410	Non-Prog	Dial	1 Heat			•		120/208/240/277 V								N/A				SPST or DPST				
	T4398	Non-Prog	Dial	1 Heat			•		120/208/240/277 V								N/A				SPST or DPST				